




Hesse SPEEDCARE-OIL OE 52872

Fast-drying, butanone oxime-free mixture of natural oils, combined with alkyd resins refined with natural oils. Special innovative and non-labeled siccatives allow it to dry extremely fast for an oil. The carefully selected, aromatic-free solvents are also used in cosmetic products. The material is Decopaint-compliant and is characterized by excellent levelling, outstanding pore wetting and a pleasant look and feel. Depending on the application quantity, open-pored, breathable surfaces or very closed-pore surfaces can be created with excellent mechanical and chemical resistance. The rapid drying feature means significant savings in production time. Since the material undergoes forced drying, the finished surfaces are stackable after a few minutes or can undergo further processing. This product does not require the usual process of rubbing in and wiping off the excess. Our SPEEDCARE-OIL impresses clients with a uniform matt look together with good wood grain accentuation and transparency.



- › very fast drying
- › accelerated drying is possible; stackable or ready for continued processing within 15 minutes

Areas of application

Suitable as a basecoat and top coat as well as for open-pore, breathable surfaces and closed-pore, lacquered surfaces with normal to heavy use. Also for stairs and handrails.

Target groups

Internal fit-out, Furniture, stairs, Special applications

Ordering information

Order number	Gloss level 60° (Gloss)	Gloss level	Container size
OE 52872	8 - 12	matt	2.5 l, 5 l, 25 l